

Conveyor Belt Group

**NEW!**  
**Conti Secur® PREMIUM**  
A contact adhesive of  
the next generation



**Strongly adhesive and economical**

# Conti Secur® PREMIUM

## The one-component adhesive

For the first time together with our partner the H.B. Fuller Company, ContiTech has succeeded in producing a one-component adhesive, Conti Secur® PREMIUM. With this new development we have fulfilled the requirements for cold bonding in conveyor technology. Continual, high adhesion strength is guaranteed, even for dynamic demands such as cold bonding of conveyor belts.


The one-component adhesive Conti Secur® PREMIUM can be used universally, just like Conti Secur® BFA. The combination of proven characteristics and new advantages makes Conti Secur® PREMIUM one of the most economical and user-friendly adhesives in the conveyor belt industry.

Use Conti Secur® PREMIUM and experience the state-of-the-art in adhesive technology.

- Can be used universally, similar to Conti Secur® BFA
- Makes warehousing and dispatch easier
- Easier processing, no activation necessary
- No sources of errors by under- or overdosage of activator
- No vulcanization in the tin
- This means the adhesive can be used completely
- Cost savings and environmental protection through waste reduction



**Note:** For the future please replace our cleaning solution RCE with our new product CCS.



The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2012 ContiTech AG. All rights reserved. For complete information go to: [www.contitech.de/disc\\_en](http://www.contitech.de/disc_en)



Narviflex NV Liesdonk 7 B-2440 Geel Tel : +32 14 59.11.31 Fax : +32 14 59.10.78	Narviflex NV Sagestraat 1 B-9042 Gent Tel : +32 9 219.93.53 Fax : +32 9 219.93.57	Narviflex SA Ch. de Charleroi (Z.I.) B-1370 Jodoigne Tel : +32 10 81.45.68 Fax : +32 10 81.27.99
---	---	--

E-Mail : [info@narviflex.be](mailto:info@narviflex.be) Web : [www.narviflex.be](http://www.narviflex.be)

Service in : Gaeß(B), Gent(B), Puurs(B), Jodoigne(B) & Echt (NL)



## Instructions for Use

# Conti Secur® PREMIUM

The one-component adhesive based on polychloroprene.

## Rubber-to-rubber adhesion

### 1. Preparation of the cold bonding

- 1.1 Clean the surface of the rubber using cleansing agent (CCS).  
Allow the cleaning agent to evaporate off for at least 10 minutes at room temperature.
- 1.2 Roughen the surface of the rubber using a grinder.

**Caution:** Minimum speed: 800 U/Min.  
Maximum speed: 2000 U/Min.

Remove the grinding dust dry.



### 2. Bonding

- 2.1 The surfaces or materials that are to be glued should preferably be at room temperature.  
If the temperature is too low, we recommend warming up the surfaces/materials.
- 2.2 First application of Conti Secur® PREMIUM onto the gluing surfaces  
Using a brush with short bristles, apply one thin coat of Conti Secur® PREMIUM to the prepared rubber surfaces.

**Drying time:** At least 30 minutes at room temperature

**Caution:** At room temperature the maximum drying time should not exceed 12 hours.

- 2.3 Second application of Conti Secur® PREMIUM to the gluing surfaces

**Drying time:** Maximum of 10 minutes at room temperature (test with back of hand).

**Note:** A third application of adhesive may be required if the surface is particularly rough.  
The drying time for the second application is then also at least 30 minutes.

- 2.4 Put the surfaces to be glued together. Press on the surfaces from the inside outwards, e.g. using a hand-held roller. The required contact pressure depends on the properties of the surfaces.

**Caution:** Brief contact pressure is sufficient. Optimum adhesion strength is attained after approx. 24 hours.

**Instructions for Use**

# Conti Secur® PREMIUM

The one-component adhesive based on polychloroprene.

## Rubber-to-metal adhesion -Contact layer material-

### 1. Preparation of the cold bonding

- 1.1 Clean the surface of the metal and the contact layer using cleansing agent (CCS).

**Caution:** If the rubber coating with the contact layer material has been stored for a longer period of time, we recommend roughening the surface of the contact layer material with a grinding disk (grade 40 or 60).

- 1.2 Roughen the metal surface by sand-blasting or with the aid of an angle grinder. Grit of the grinding disk: 16 or 24. Remove the grinding dust dry.

### 2. Bonding

- 2.1 Thoroughly stir the adhesive agent CONTI PLUS® prior to processing, and apply one thin coat to the metal surface.

**Drying time:** At least 30 minutes at room temperature

**Caution:** Coated parts can be stored up to a maximum of 2 weeks at room temperature.

- 2.2 Apply one coat of Conti Secur® PREMIUM to the metal surface.

**Drying time:** At least 30 minutes at room temperature

**Caution:** Do not use a brush with short bristles, as otherwise the CONTI PLUS® coating could come off again.

- 2.3 Cut the rubber coating to size.  
Second application of Conti Secur® PREMIUM on the metal surface.
- 2.4 One coating of Conti Secur® PREMIUM onto the surface of the contact layer.

**Drying time:** Maximum of 10 minutes (test with back of hand).

- 2.5 Put the coated surfaces together. Press on the surfaces from the inside outwards, e.g. using a hand-held roller or a dead-blow hammer.

**Caution:** Brief contact pressure is sufficient.  
Optimum adhesion strength is attained after approx. 24 hours.



The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2012 ContiTech AG. All rights reserved. For complete information go to: [www.contitech.de/disc1\\_en](http://www.contitech.de/disc1_en)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.07.2012







Version number 1

Revision: 13.07.2012

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name** CONTI SECUR PREMIUM
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC1 Adhesives, sealants
- **Application of the substance / the preparation** Adhesives
- **Details of the supplier of the safety data sheet** CONTINENTAL - CONTITECH
- **Manufacturer/Supplier:**  
H.B. Fuller Austria Produktions GesmbH  
Kaplanstraße 30  
A-4600 Wels  
Tel.Nr. +43 (0) 7242/211770-0  
EU-MSDS@hbfuller.com
- **Informing department:** Regulatory department
- **Emergency telephone number:** +44 (0) 1235 239 670 (24 hours)

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
  -  Xi; Irritant  
R36/38: Irritating to eyes and skin.
  -  F; Highly flammable  
R11: Highly flammable.
  -  N; Dangerous for the environment  
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67: Vapours may cause drowsiness and dizziness.
- **Information concerning particular hazards for human and environment:** Has a narcotic effect.
- **Classification system:**  
The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.
- **Label elements**
- **Labelling according to EU guidelines:**  
The product has been classified and labelled in accordance with EC Directives / Chemicals (Hazard, Information and Packaging for Supply) (CHIP) Regulations.
- **Code letter and hazard designation of product:**
  -  Xi Irritant
  -  F Highly flammable
  -  N Dangerous for the environment
- **Risk phrases:**
  - 11 Highly flammable.
  - 36/38 Irritating to eyes and skin.
  - 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - 67 Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 1)

- **Safety phrases:**

- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe vapour.
- 24/25 Avoid contact with skin and eyes.
- 33 Take precautionary measures against static discharges.
- 57 Use appropriate container to avoid environmental contamination.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

- **Special labelling of certain preparations:**

Contains Rosin. May produce an allergic reaction.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:**

Solvent based adhesive, based on Polychloroprene

- **Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-0000	ethyl acetate Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119486291-36-0000	cyclohexane Xn R65; Xi R38; F R11; N R50/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-0000	acetone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
	hexane, mixture of isomers (containing less than 5 % n-hexane EEC No 203-777-6) Xn R65; Xi R38; F R11; N R51/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	< 5%
CAS: 142-82-5 EINECS: 205-563-8 Reg.nr.: 01-2119475515-33-0000	heptane Xn R65; Xi R38; F R11; N R50/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	< 5%

(Contd. on page 3)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 2)

CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119489801-30-0000	Carbon black substance with a Community workplace exposure limit	< 2.5%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Xn R48/20-62-65; Xi R38; F R11; N R51/53 R67 Repr. Cat. 3 Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0.5-1%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32-0000	Rosin Xi R43 Skin Sens. 1, H317	0.5-1%
CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	< 0.5%

· **Additional information** For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

- **Description of first aid measures**
- **General information**  
Instantly remove any clothing soiled by the product.  
Take affected persons into the open air.
- **After inhalation**  
In case of unconsciousness bring patient into stable side position for transport.  
Supply fresh air.
- **After skin contact**  
Instantly wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact**  
Rinse opened eye for several minutes (15 min) under running water. Then consult doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents**  
Water haze  
Foam  
Fire-extinguishing powder  
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter drains.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
 Ensure adequate ventilation  
 Keep away from ignition sources  
 Use breathing protection against the effects of fumes/dust/aerosol.  
 Wear protective clothing.

- **Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.  
 Inform respective authorities in case product reaches water or sewage system.  
 Do not allow to enter drainage system, surface or ground water.

- **Methods and material for containment and cleaning up:**

Ensure adequate ventilation.  
 Send for recovery or disposal in suitable containers.  
 Use non sparking handtools.  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders)

- **Reference to other sections**

See Section 8 for information on personal protection equipment.

### 7 Handling and storage

- **Handling**

- **Precautions for safe handling**

Store in cool, dry place in tightly closed containers.  
 Ensure good ventilation/exhaustion at the workplace.  
 Ensure that suitable extractors are available on processing machines  
 Take note of emission threshold.  
 Use solvent-proof equipment.  
 Keep away from children  
 Avoid release to the environment.  
 Keep eye wash bottles available on working place.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
 Protect from heat.  
 Protect against electrostatic charges.  
 Highly volatile, flammable constituents are released during processing.  
 Fumes can combine with air to form an explosive mixture.  
 Flammable mixtures may be formed in empty containers.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and containers:**

Store in cool location.  
 Keep dark, cool and dry.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed containers.

- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:**

Please take care on national and local requirements.

(Contd. on page 5)



## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 4)

#### · Control parameters

##### · Components with critical values that require monitoring at the workplace:

141-78-6 ethyl acetate	
WEL	Short-term value: 400 ppm Long-term value: 200 ppm
110-82-7 cyclohexane	
WEL	Short-term value: 1050 mg/m <sup>3</sup> , 300 ppm Long-term value: 350 mg/m <sup>3</sup> , 100 ppm
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
142-82-5 heptane	
WEL	Long-term value: 500 ppm
1333-86-4 Carbon black	
WEL	Short-term value: 7 mg/m <sup>3</sup> Long-term value: 3.5 mg/m <sup>3</sup>

#### · DNELs

##### ETHYL ACETATE:

Human exposure:

DNEL: 1468 mg/m<sup>3</sup> (acute systemic effects; inhalation; workers)DNEL: 1468 mg/m<sup>3</sup> (acute local effects; inhalation; workers)DNEL: 734 mg/m<sup>3</sup> (long-term systemic effects; inhalation; workers)DNEL: 734 mg/m<sup>3</sup> (long-term local effects; inhalation; workers)

DNEL: 63 mg/kg body weight/day (long-term systemic effects; dermal; workers)

DNEL: 734 mg/m<sup>3</sup> (acute systemic effects; inhalation; general population)DNEL: 734 mg/m<sup>3</sup> (acute local effects; inhalation; general population)DNEL: 367 mg/m<sup>3</sup> (long-term systemic effects; inhalation; general population)

DNEL: 4,5 mg/kg body weight/day (long-term systemic effects; oral; general population)

DNEL: 367 mg/m<sup>3</sup> (long-term local effects; inhalation; general population)

DNEL: 37 mg/kg body weight/day (long-term systemic effects; dermal; general population)

##### ACETONE

DNEL Long term Dermal 186 mg/kg bw/day Workers -

DNEL Short term Inhalation 2420 mg/m<sup>3</sup> Workers -DNEL Long term Inhalation 1210 mg/m<sup>3</sup> Workers -

DNEL Long term Oral 62 mg/kg bw/day Consumers -

DNEL Long term Dermal 62 mg/kg bw/day Consumers -

DNEL Long term Inhalation 200 mg/m<sup>3</sup> Consumers

CYCLOALKANE: (Kohlenwasserstoffe, C6-C7, Isoalkane, Cyclene, &lt;5% n-Hexan)

Arbeiter

Dermal

13964 mg/kg bw/day DNEL, Chronisch Exposition, Systemisch Effekte

Inhalierung

5306 mg/m<sup>3</sup> DNEL, Chronisch Exposition, Systemisch Effekte

#### · PNECs

##### ETHYL ACETATE:

Environment:

PNEC (freshwater): 0.26 mg/L (based on the lowest chronic toxicity value NOEC = 2.6 mg/L for invertebrates and assessment factor 10).

PNEC (saltwater): 0.026 mg/L (based on the lowest chronic toxicity value NOEC = 2.6 mg/L for invertebrates and assessment factor 100).

PNEC (intermittent releases): 1.65 mg/L (based on the lowest aquatic toxicity value EC50 = 165 mg/L for invertebrates and assessment factor 100).

PNEC (sediment, freshwater): 1.25 mg/kg dry weight (based on partition coefficient method).

PNEC (sediment, saltwater): 0.125 mg/kg dry weight (based on partition coefficient method).

PNEC (soil): 0.24 mg/kg dry weight (based on partition coefficient method).

PNEC (sewage treatment plant): 650 mg/L (based on the lowest effect concentration for micro-

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

#### Trade name CONTI SECUR PREMIUM

(Contd. of page 5)

organisms EC10 = 650 mg/L and assessment factor 1).

ACETONE

PNEC Marine 1,06 mg/l -

PNEC Fresh water 10,6 mg/l -

PNEC Fresh water sediment 30,4 mg/l -

PNEC Marine water sediment 3,04 mg/l -

PNEC Soil 0,112 mg/l -

PNEC Sewage Treatment Plant 29,5 mg/l -

CYCLOALKANE: (Kohlenwasserstoffe, C6-C7, Isoalkane, Cyclene, <5% n-Hexan)

NA

· **Additional information:** Based on information valid at the time of writing.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feedingstuffs.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Not necessary if room is well-ventilated.

Ensure that suitable extractors are available on processing machines

· **Recommended filter device for short term use:** Filter AX

· **Protection of hands:**

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves:** Butyl rubber, BR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed safety glasses.

· **Body protection:** Protective work clothing.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: According to product specification

· **Smell:** Characteristic

· **Change in condition**

Melting point/Melting range: Not determined

Boiling point/Boiling range: 56 °C

· **Flash point:** -19 °C

· **Ignition temperature:** 260 °C

· **Self-inflammability:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive vapour/ air mixtures is possible.

(Contd. on page 7)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 6)

- **Critical values for explosion:**

<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	11.5 Vol %

- **Vapour pressure at 20 °C:** 104 hPa

- **Density at 20 °C:** 0.86 g/cm<sup>3</sup>
- **Water:** Not miscible or difficult to mix

- **Viscosity:**
- dynamic at 20 °C:** 1500 mPas

- **Solvent content:**
- Organic solvents:** 73.5 %

- Solids content:** 25.5 - 27.5 %
- **Other information:** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** Develops readily flammable vapours / fumes
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

<b>110-82-7 cyclohexane</b>		
Oral	LD50	1297 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant for skin and mucous membranes.
- **on the eye:** Irritant effect.
- **Sensitization:** No sensitizing effect known.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:  
Irritant

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish

(Contd. on page 8)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**  
Also poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms  
Danger to drinking water if even small quantities leak into soil.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
Hand over to disposers of hazardous waste.  
Incineration under approved, controlled conditions using incinerators suitable or designed for the disposal of hazardous chemical wastes, is the preferred method for disposal.

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
-----------	--

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                       |  |
|---------------------------------------|--|
| · <b>UN-Number</b>                    | UN1133   |
| · <b>ADR, IMDG, IATA</b>              | UN1133   |
| · <b>UN proper shipping name</b>      | 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS  |
| · <b>ADR</b>                          | ADHESIVES (CYCLOHEXANE, hexane, mixture of isomers (containing less than 5 % n-hexane EEC No 203-777-6)), MARINE POLLUTANT |
| · <b>IMDG</b>                         | ADHESIVES  |
| · <b>IATA</b>                         | ADHESIVES  |
| · <b>Transport hazard class(es)</b>   |  |
| · <b>ADR, IMDG, IATA</b>              | 3 Flammable liquids.   |
| · <b>Class</b>                        | 3  |
| · <b>Label</b>                        |  |
| · <b>Packing group</b>                | II   |
| · <b>ADR, IMDG, IATA</b>              |  |
| · <b>Environmental hazards:</b>       | Product contains environmentally hazardous substances:   |
| · <b>Marine pollutant:</b>            | Yes  |
| · <b>Special marking (ADR):</b>       | Symbol (fish and tree)   |
|                                       | Symbol (fish and tree)   |
| · <b>Special precautions for user</b> | Warning: Flammable liquids.  |
| · <b>Kemler Number:</b>               | 33   |
| · <b>EMS Number:</b>                  | F-E,S-D  |

(Contd. on page 9)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

Trade name CONTI SECUR PREMIUM

(Contd. of page 8)

- |  |   |
|--|---|
| <b>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                           |
| <b>· Transport/Additional information:</b>                                       |   |
| <b>· ADR</b>   |   |
| <b>· Tunnel restriction code</b>   | D/E                                       |
| <b>· IMDG</b>  |   |
| <b>· Remarks:</b>  | Suitable UN approved container necessary. |
| <b>· IATA</b>  |   |
| <b>· Remarks:</b>  | Suitable UN approved container necessary. |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Other regulations, limitations and prohibitive regulations**
- **VOC (EU) in %:** 74.26 %
- **VOC (EU) in g/l:** 638.6 g/l
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The information provided about the product on this Safety Sheet has been compiled from knowledge of the individual constituent.

The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R62 Possible risk of impaired fertility.
- R65 Harmful: may cause lung damage if swallowed.

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

**Trade name CONTI SECUR PREMIUM**

(Contd. of page 9)

R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

- **Department issuing data sheet:** Regulatory department
- **Contact:** EU-MSDS@hbfuller.com
- \* **Data compared to the previous version altered.**

GB

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 14.07.2012

Version number 1

Revision: 13.07.2012

**Trade name CONTI SECUR PREMIUM**

(Contd. of page 10)

**Annex: Exposure scenario**

GB



Narviflex NV	Narviflex NV	Narviflex SA
Liesdonk 7	Sagastraat 1	Ch. de Charleroi (Z.I.)
B-2440 Geel	B-9042 Gent	B-1370 Jodoigne
Tel : +32 14 59.11.31	Tel : +32 9 219.93.53	Tél : +32 10 81.45.68
Fax : +32 14 59.10.76	Fax : +32 9 219.93.57	Fax : +32 10 81.27.99

E-Mail : [info@narviflex.be](mailto:info@narviflex.be) Web : [www.narviflex.be](http://www.narviflex.be)

Service in : Geel(B), Gent(B), Puurs(B), Jodoigne(B) &amp; Echt (NL)